


Strobe light, hide away 12/24V

Instruction manual



FEATURES

- Two mounting holes, accessible from the front or rear side of the lamp
- Operating voltage 10~30 VDC
- 19 flash patterns

OPERATING INSTRUCTION

- Connect RED wire to + VDC – Fuse @2A.
- Connect BLACK wire to chassis ground.
- Tap BLUE wire to BLACK wire quickly to select next flash pattern.
- Tap BLUE wire to BLACK wire for more than 5 sec. to turn the unit off.

DIM MODE

- Connect the WHITE colour wire to GND to DIM the strobe light; this will reduce the brightness by 30% from the original.

SYNCHRONISED FLASH

- Connect YELLOW wires of all units together and set all units to the required synchronised pattern.

ALTERNATE FLASH

- Connect YELLOW wires of all units together and set all units to either phase 1 or phase 2 of that alternate pattern. Units set on phase 1 will alternate with units set on phase 2.

FLASH PATTERN

PA1	Single Flash 75FPM Sim. PH1
PA2	Single Flash 75FPM Sim. PH2
PA3	Single Flash 75FPM ALT
PA4	Double Flash 75FPM SIM. PH1
PA5	Double Flash 75FPM SIM. PH2
PA6	Double Flash 75FPM ALT
PA7	Quad Flash 75FPM Sim. PH1
PA8	Quad Flash 75FPM Sim. PH2
PA9	Quad Flash 75FPM ALT
PA10	Single Flash 120FPM Sim. PH1
PA11	Single Flash 120FPM Sim. PH2
PA12	Single Flash 120FPM ALT
PA13	Double Flash 120FPM Sim. PH1
PA14	Double Flash 120FPM Sim. PH2
PA15	Double Flash 120FPM ALT
PA16	Quad Flash 150FPM Sim. PH1
PA17	Quad Flash 150FPM Sim. PH2
PA18	Quad Flash 150FPM Sim. ALT
PA19	Steady Burn